

**Ribble Enviro**  
*...everything gas detection*

# Data Sheet

[sales@ribble-enviro.co.uk](mailto:sales@ribble-enviro.co.uk)

+44(0)1200 445 804

[ribble-enviro.co.uk](http://ribble-enviro.co.uk)

Unit 4, Business Park, Gisburn, Clitheroe BB7 4JP

Company No: 06140589 VAT No: GB 906 6241 34

# XGARD BRIGHT

## Addressable Fixed Point Gas Detector with Display

Non-intrusive calibration  
MODBUS, HART & relay options



Xgard Bright is a versatile platform designed for detecting flammable and toxic gases, as well as monitoring oxygen levels.

The 4-wire addressable implementation minimizes cabling requirements, lowering installation costs. The large OLED display ensures users can easily interact with Xgard Bright during installation, calibration, and routine maintenance without opening the housing.

### FEATURES

#### Long-life Sensors

Choose from robust sensor options such as MPS (10+ years), O2 Long-life (5 years), and IR sensors (10+ years) to reduce the frequency of sensor replacements and minimize operational expenses.

#### Flexible Communication

Xgard Bright supports connection to an addressable network using Modbus RS-485 RTU, alongside analogue 4-20 mA output. This setup reduces cable and installation costs while enhancing system flexibility and functionality. HART communication is also available as an option.

#### OLED Display

The bright OLED display clearly shows gas levels and units, providing comprehensive menus for setup and diagnostics. In low-light conditions, the OLED display offers a higher contrast ratio than conventional LCDs, making it easier to read.

#### Non-intrusive Calibration

Zero and calibration functions, along with setup, tests, and adjustments, are performed via the display using a magnetic wand, eliminating the need to open the housing and reducing the requirement for a hot-work permit.

### GAS RANGES & ALARMS

GAS	SENSOR	RANGES AVAILABLE	TEMP. RANGE
Flammable gases*	MPS	0-100% LEL	-40 to +75 °C
Butane (C <sub>4</sub> H <sub>10</sub> )	Infrared	0-100% LEL	-40 to +60°C
Hydrogen (H <sub>2</sub> )	Catalytic	0-100% LEL	-40 to +70°C
LPG	Catalytic Infrared	0-100% LEL	-40 to +70°C -40 to +60°C
Methane (CH <sub>4</sub> )	Catalytic Infrared	0-100% LEL	-40 to +70°C -40 to +60°C
Pentane (C <sub>5</sub> H <sub>12</sub> )	Catalytic Infrared	0-100% LEL	-40 to +70°C -40 to +60°C
Propane (C <sub>3</sub> H <sub>8</sub> )	Catalytic*** Infrared	0-100% LEL	-40 to +70°C -40 to +60°C
Carbon Monoxide (CO)	Electrochemical	0-25, 50, 100, 200, 250, 300, 1000, 2000 ppm	-30 to +50°C
Hydrogen sulphide (H <sub>2</sub> S)	Electrochemical	10, 20, 25, 50, 100, 200 ppm	-40 to +50°C
Oxygen (O <sub>2</sub> ) - Long Life Lead Free	Electrochemical	0-25% vol	-40 to +60°C
Oxygen (O <sub>2</sub> )	Electrochemical	0-25% vol	-20 to +50°C
Carbon Dioxide (CO <sub>2</sub> )	Infrared	0-5% vol	-40 to +60°C

\* Contact Crowcon for more information  
\*\*\* Contact Crowcon for availability



# SPECIFICATIONS

<b>ENCLOSURE MATERIAL</b>	ADC 12 aluminium alloy or 316 stainless steel	
<b>DIMENSIONS</b>	<b>Aluminium Enclosure</b> ATEX/IECEX: 156 x 166 x 109 mm (6.1 x 6.5 x 4.3 inch) UL: 162 x 166 x 110 mm (6.4 x 6.5 x 4.3 inch) <b>Stainless Steel Enclosure</b> ATEX/IECEX: 165 x 166 x 105 mm (6.1 x 6.5 x 4.1 inch) UL: 162 x 166 x 103 mm (6.4 x 6.5 x 4.1 inch)	
<b>WEIGHT</b>	<b>Aluminium enclosure</b> ATEX/IECEX: 1kg (2.2 lbs) UL: 1.5 kg (3.31 lbs) <b>Stainless Steel enclosure</b> ATEX/IECEX: 3.1 kg (6.8 lbs) UL: 3.5 kg (7.72 lbs)	
<b>INGRESS PROTECTION</b>	IP65/66, EN 60529	
<b>CABLE ENTRY</b>	2x M20 or 2x ½" NPT (Stopping plug fitted to the left-side entry)	
<b>OPERATING VOLTAGE</b>	10-30Vdc. 3W max	
<b>POWER</b>	3W max	
<b>ELECTRICAL OUTPUT</b>	3-wire 4-20mA (Sink or Source) RS-485 Modbus RTU HART 7 (Optional)	
<b>RELAY OUTPUT</b>	Alarm 1, Alarm 2, Fault (SPDT Contacts. Rated 1A, 24Vdc)	
<b>SOUNDER</b>	High Side Switch (24V nominal, 12V minimum, 700mA maximum load)	
<b>OPERATING TEMPERATURE</b>	ATEX/IECEX: -40°C to +70°C (-40°F to 158°F) UL: -40°C to +60°C (-40°F to 140°F)	
<b>HUMIDITY</b>	0 to 95% RH (non-condensing) Contact Crowcon for sensor operating humidity range.	
<b>REPEATABILITY</b>	Repeatability: +/- 2% FSD Zero drift: +/- <2% FSD per year	
<b>EMC COMPLIANCE</b>	EN 50270, EN IEC 61326-1, EN 55011, CISPR 11, EN 61000-4	
<b>HAZLOC STANDARDS AND APPROVALS</b>	<b>ATEX:</b> EN IEC 60079-0, EN 60079-1, EN 60079-31 <b>IECEX:</b> IEC 60079-0, IEC 60079-1, IEC 60079-31 Zone 1 and Zone 2 or Zone 21 and Zone 22 <b>Aluminium:</b> Ex II 2 G Ex db IIC T6 Gb Tamb: -40°C≤Ta≤70 °C Ex II 2 D Ex tb IIIC T80°C Db Ex db IIC T6 Gb Tamb: -40°C≤Ta≤70 °C Ex tb IIIC T80°C Db	<b>Stainless Steel:</b> Ex II 2 G Ex db IIC T3 Gb Tamb: -40°C≤Ta≤70 °C Ex II 2 G Ex db IIC T4 Gb Tamb: -40°C≤Ta≤50°C Ex II 2 D Ex tb IIIC T80°C Db Ex db IIC T3 Gb Tamb: -40°C≤Ta≤70°C Ex db IIC T4 Gb Tamb: -40°C≤Ta≤50°C Ex tb IIIC T80°C Db <b>UL:</b> UL 1203 -40°C≤Ta≤60 °C Class I, Division 1, Groups B, C, D T6 Class II Division 1, Groups E, F, G T6
<b>APPROVALS</b>	UL, IECEX, ATEX, CE, ECAS, PESO, CNEx, UC, CCS TA, MED***	
<b>PERFORMANCE</b>	UL 60079-29-1**	
<b>WARRANTY</b>	2 years on transmitter 5 years on MPS flammable and O2 Long Life sensor 2 years on IR flammable sensors Refer to GEN067 – Warranty Periods for other sensors	

\*\*pending

## Disclaimer

Due to ongoing research and product improvement, specifications are subject to change without notice. While every effort has been made to ensure accuracy in this document, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines.

This document is not intended to form the basis of a contract.

### For more information:

t: +44 (0)1235 557700

e: info@crowcon.com

w: www.crowcon.com

Locate your Regional Sales Representative at:

www.crowcon.com/contact-us/where-to-buy

© 2025 Crowcon Detection Instruments Ltd.