

Ribble Enviro
...everything gas detection

Data Sheet

sales@ribble-enviro.co.uk

+44(0)1200 445 804

ribble-enviro.co.uk

Unit 4, Business Park, Gisburn, Clitheroe BB7 4JP

Company No: 06140589 VAT No: GB 906 6241 34



Dräger X-am 5600 Multi-Gas Detector

Featuring an ergonomic design and innovative infrared sensor technology, the Dräger X-am 5600 is one of the smallest gas detection instrument for the measurement of up to 6 gases. Ideal for personal monitoring applications, this robust and water-tight detector provides accurate, reliable measurements of flammable and toxic gases and vapors as well as oxygen.

Dräger X-am 5600

Safe gas entry
Gas entry from two sides

Visual alarm
360° visible alarm

Crocodile clip
Secure attachment

DrägerSensors
Quick, precise, long service life

Robust design
Water and dust resistant
in acc. with IP 67

Large display
All values at a glance

D-23637-2009



Benefits

Small yet robust

Small, light and easy to use – the robust and water-tight gas detector X-am 5600 is designed for single-handed operation in tough industrial environments. Water- and dustproof according to IP 67 and with an integrated rubber boot, the device provides optimal functionality even under harsh conditions.

Durable infrared technology

Thanks to the high stability and a resistance to contamination, Dräger infrared sensors can generally be used for up to eight years. This advanced technology reduces the cost of ownership considerably because less replacement sensors are needed. In addition, a calibration of the IR sensor is only necessary every 12 months which reduces maintenance costs.

Single or dual sensor – accurate measurement results

The infrared sensor IR Ex allows the measurement of flammable hydrocarbons in the range of the lower explosive limit. The infrared sensor IR CO₂, with a measurement resolution of 0.01 Vol.-%, provides safe and exact measurements as well as a warning against toxic concentrations of carbon dioxide in the ambient air. For those applications where the reliable measurement of flammable substances and CO₂ is specifically needed, the advantages of both can be achieved by a dual sensor (Dual IR CO₂/Ex).

Also in combination with Hydrogen

Besides hydrocarbons, hydrogen can also be a flammable gas. Because sensors based on infrared technology do not warn against hydrogen explosion dangers, the gas detector X-am 5600 combines two sensor signals (Infrared Ex and electrochemical H₂HC) for reliable hydrogen detection. The X-am 5600 provides the advantages of poison-free technology to be used in areas where, until now, only catalytic Ex sensors have been used.

Various monitoring possibilities

Thanks to the combination of innovative infrared technology and the latest electrochemical Dräger XXS miniature sensors, this 1-to-6 gas detector reliably detects flammable and harmful concentrations of O₂, Cl₂, CO, CO₂, H₂, H₂S, HCN, NH₃, NO, NO₂, PH₃, SO₂, O₃, Amine, Odorant, COCl₂ and organic vapors. With the PC software Dräger CC-Vision, the sensors can easily be exchanged, calibrated or converted to meet the needs of different applications.

Flexible use

An optional external pump which can be operated with hoses up to 45 m in length is the perfect solution for pre-entry measurements in tanks or pipelines. To monitor entire areas, the gas detector X-am 5600 can be used in combination with the highly visible area monitor Dräger X-zone 5500/5800.

Suitable for Ex-Zone 0

The small and reliable gas detector is suitable for use in areas classified as zone 0, which are areas where explosive atmospheres are always to be expected – also with Dräger X-am Pump and Dräger X-zone 5500/5800.

Benefits

Area monitoring

In combination with the Dräger X-zone 5500/5800 the gas detector can be used for various area monitoring applications. Up to 25 Dräger X-zone 5500/5800 units can be automatically interconnected to form a wireless fence. This interconnection of the area monitoring devices allows for the fast securing of larger areas, e.g. pipelines or industrial tanks – even within the scope of industrial shutdowns.

System Components



D-12191-2010

DrägerSensor XXS

Dräger has developed miniature electrochemical sensors specially for the Dräger Pac, X-am 1/2/5 and X-am 8000 generation. The sensors detect many different gases and vapours. They are also very reliable and stable over the long-term, thereby reducing your operating costs.



D-21105-2011

Dräger Infrared Sensors

Dräger infrared sensors deliver optimal measurement results and are unaffected by sensor poisons. The long service life of these sensors results in hardly any follow-up costs. You can also use Dräger infrared sensors to take Ex and CO₂ measurements simultaneously.

System Components

D-47907-2012



Dräger X-dock 5300/6300/6600

The Dräger X-dock series provides you with full control of your portable Dräger gas detection instruments. Automatic bump tests and calibrations with reduced test gas consumption and short testing times save time and money. Comprehensive documentation and evaluations provide you with a clear overview.


D-24997-2020



Dräger Bump Test Station

Easy to use, stand-alone and portable. With the Bump Test Station, functionality tests of gas detection and warning devices can be carried out easily and quickly.

D-40484-2021



Gas Detection Connect

Dräger Gas Detection Connect is your connection to the digital future of occupational safety. The system connects individual Dräger products through a smart software solution. Thanks to location- and time-independent access, you manage your equipment optimally and always have the position and status of your gas detection equipment and workers available. So you can protect your workforce and increase the efficiency of your plant at the same time.

Accessories

D-0494-2018



Calibration gas and accessories

Calibration of equipment will ensure safe operation and functionality of equipment and will also meet with the applicable regulations and codes of practice. Various calibration options are easily available.

D-30746-2015



Dräger Configuration and Evaluation Software

Save measurement results, professionally configure gas detection instruments and viewing performance data – all that is possible with the tailor-made Dräger software.

D-11857-2016



Dräger X-am Pump

The Dräger X-am Pump is an external pump for the portable gas detectors Dräger X-am 2500/2800 and X-am 5000/5600/5800 – designed for clearance measurement, for example in tanks and shafts. The pump automatically switches on when it is connected to a running X-am device. The change from pump mode to diffusion mode is fast and easy.

D-12284-2009



Power pack & Charging set

Consisting of: NiMH power supply, charging module, single charger

Accessories

ST-14360-2008



Calibration cradle

Related Products

D-14325-2017



Dräger X-am 5000

The Dräger X-am 5000 belongs to a generation of gas detectors, developed especially for personal monitoring applications. This 1- to 5-gas detector reliably measures combustible gases and vapors as well as oxygen and harmful concentrations of toxic gases, organic vapors, Odorant and Amine.

D-9538-2022



Dräger X-am 5800

The X-am 5800 multi-gas detector measures up to six gases and is equipped with a particularly shock-resistant CatEx sensor. With the Dräger Gas Detection Connect software, it offers live data transmission and powerful asset management. Designed for personal monitoring, the X-am 5800 offers you the highest level of safety at a low cost of ownership.

Technical Data

Dimensions (W x H x D)		48 x 130 x 44 mm	
Weight		220 – 250 g	
Ambient conditions	Temperature	-20 to +50 °C -40 °C possible over a short period (ATEX & IECEx only), max. 15 minutes with NiMH supply unit T4 (HBT 0000) or T4 HC (HBT 0100), prerequisite: storage of the device at room temperature at room temperature (+20 °C) for at least 60 minutes.	
	Pressure	700 to 1,300 mbar	
	Relative humidity	10 to 95 % r.h.	
Protection class		IP 67	
Alarms	Visual	360°	
	Audible	Multi-tone > 90 dB at 30 cm	
	Vibration		
Operating times		~ 12 h >250 h without Ex Sensor	
Charging time		< 4 h	
Datalogger		Application of an optimized data compression method with high accuracy and large storage capacity (typically data compression >90% compared to the traditional data logger concept with adjustable interval)	
Pump operation		Maximum hose length 45 m; 148 ft.	
Approvals	ATEX	II 1G Ex da ia IIC T4/T3 Ga, I M1 Ex da ia I Ma	
	IECEx	Ex da ia IIC T4/T3 Ga, Ex da ia I Ma	
	CSA (Canada & USA)	Class I, Div. 1, Groups A, B, C, D Class II, Div. 1, Groups E, F, G Class I, Zone 0, A/Ex da ia IIC T4/T3 Ga	
	Measurement performance certificate	EN 50104	O ₂
		EN 45544-1, EN 45544-2	CO & H ₂ S
		EN 60079-29-1	Methane to nonane, XXS H ₂ HC
	CE mark		Electromagnetic Compatibility (Directive 2014/30/EU)
MED		Marine Equipment Directive (Directive 2014/90/EU)	
MER		Merchant Shipping (Marine Equipment) Regulations 2016	
EAC		PO Ex ia I Ma X 0Ex ia IIC T4/T3 Ga X	

Ordering Information

Dräger X-am 5600

83 21 050

Consisting of: basic instrument with an integrated data logger. A functional instrument must include up to 4 sensors and a power supply unit (option).

Infrared sensors	Measuring range	Resolution	Order code
Dual IR Ex/CO ₂ ES ¹	0 – 100 % LEL 0 – 100 Vol.-% Methane, Propane, Ethene, n-Butane 0 – 5 Vol.-% CO ₂	1 % LEL 0.1 Vol.-% CH ₄ 0.01 Vol.-% CO ₂	68 51 880
IR Ex ES ¹	0 – 100 % LEL 0 – 100 Vol.-% Methane, Propane, Ethene, n-Butane	1 % LEL 0.1 Vol.-% CH ₄	68 51 881
IR CO ₂ ES	0 – 5 Vol.-% CO ₂	0.01 Vol.-% CO ₂	68 51 882

Electrochemical sensors	Measuring range	Resolution	Order code
XXS O ₂ ²	0 – 25 Vol.-%	0.1 Vol.-%	68 10 881
XXS CO LC	0 – 2,000 ppm	1 ppm	68 13 210
XXS O ₂ 100	0 – 100 Vol.-%	0.5 Vol.-%	68 12 385
XXS O ₂ PR	0 – 30 Vol.-%	0,1 Vol.-%	68 00 530
XXS CO HC	0 – 10,000 ppm	5 ppm	68 12 010
XXS CO/H ₂ compensated	0 – 2,000 ppm CO	2 ppm	68 11 950
XXS H ₂ S LC ²	0 – 200 ppm	0.1 ppm	68 11 525
XXS H ₂ S HC	0 – 1,000 ppm	2 ppm	68 12 015
XXS CO LC/H ₂ S LC	0 – 2,000 ppm CO 0 – 200 ppm H ₂ S	1 ppm CO 0.1 ppm H ₂ S	68 13 280
XXS CO LC/O ₂	0 – 200 ppm CO 0 – 25 Vol.-% O ₂	1 ppm CO 0.1 Vol.-% O ₂	68 13 275
XXS H ₂ S LC/O ₂	0 – 100 ppm H ₂ S 0 – 25 Vol.-% O ₂	0.1 ppm H ₂ S 0.1 Vol.-% O ₂	68 14 137
XXS NO	0 – 200 ppm	0.1 ppm	68 11 545
XXS NO ₂	0 – 50 ppm	0.1 ppm	68 10 884
XXS NO ₂ LC	0 – 50 ppm	0.02 ppm	68 12 600
XXS SO ₂	0 – 100 ppm	0.1 ppm	68 10 885
XXS PH ₃	0 – 20 ppm	0.01 ppm	68 10 886
XXS PH ₃ HC	0 – 2,000 ppm	1 ppm	68 12 020
XXS HCN	0 – 50 ppm	0.1 ppm	68 10 887
XXS HCN PC	0 – 50 ppm	0.5 ppm	68 13 165
XXS NH ₃	0 – 300 ppm	1 ppm	68 10 888
XXS CO ₂	0 – 5 Vol.-%	0.1 Vol.-%	68 10 889

Ordering Information

XXS Cl ₂	0 – 20 ppm	0.05 ppm	68 10 890
XXS H ₂	0 – 2,000 ppm	5 ppm	68 12 370
XXS H ₂ HC	0 – 4 Vol.-%	0.01 Vol.-%	68 12 025
XXS OV	0 – 200 ppm	0.5 ppm	68 11 530
XXS OV-A	0 – 200 ppm	1 ppm	68 11 535
XXS Amine	0 – 100 ppm	1 ppm	68 12 545
XXS Odorant	0 – 40 ppm	0.5 ppm	68 12 535
XXS COCl ₂	0 – 10 ppm	0.01ppm	68 12 005
XXS Ozone	0 – 10 ppm	0.01 ppm	68 11 540

ES = Energy saving

HC = High concentration

¹ Special calibrations possible for the Ex sensors (Standard: methane).

² Dräger provides a 3 year manufacturer's warranty on the Dräger X-am 5000 and these sensors. The legal rights arising from defects remain unaffected.

Power supply units

NiMH power supply T4 2.0	37 03 887
Power pack & charging set consisting of: rechargeable NiMH power supply T4 2.0, charging module and a single charger (for worldwide use)	37 03 889
Battery holder ABT 0100 (without batteries)	83 22 237
Alkaline batteries T3 (2 pcs.) for battery holder 83 22 237	83 22 239

Charging accessories

Charging module	83 18 639
Charging set basic, consisting of one charging module and a single power supply (worldwide use)	83 20 333
Power plug 100–240 VAC; 6.25 A, for charging up to 20 devices Adapter for power plug 83 25 736 is needed in addition.	83 21 850
Single charger (worldwide use) for max. 5 charger modules	83 16 994
Car charging connection cable 12 V / 24 V for a charging module	45 30 057
Vehicle charger mounting kit for one Dräger X-am 1/2/5x00 charging module	83 18 779
Charging adapter for charging a rechargeable battery without X-am device	83 26 101

Ordering Information

Pump accessories

Dräger X-am Pump (external pump)	83 27 100
Dräger X-am Pump incl. USB charger and shoulder strap	83 27 115
Hand pump adapter	83 19 195
CSE Set Dräger X-am Pump (incl. 5 m FKM hose)	83 27 117
Case for Dräger X-am Pump	83 27 104

Calibration accessories

Calibration cradle	83 18 752
Dräger X-dock 5300 for Dräger X-am 1/2/5x00	83 21 880
Dräger Bump Test Station for Dräger X-am 5600, not including gas cylinder	83 19 131
Dräger Bump Test Station for Dräger X-am 5600, complete with one test gas cylinder 58L (gas and concentration variable)	83 19 130
Nonane Checker	83 20 080

Communication accessories / software

Dräger GasVision license key	83 25 646 software: www.draeger.com/software (free trial version)
Dräger CC-Vision	www.draeger.com/software
USB DIRA with USB cable, communication adapter infrared to USB	83 17 409

Area monitoring

Dräger X-zone 5500, 868 MHz, 24 Ah battery with diffusion cap	83 24 819
Dräger X-zone 5800 with integrated pump, 868 MHz, 24 Ah battery with diffusion and pump cap	83 29 030

In conjunction with the portable alarm amplifier Dräger X-zone 5500/5800, the devices are combined into system, e.g. to monitor entire work areas or to switch the alarm contact to external equipment.

Not all products, features, or services are for sale in all countries. Trademarks mentioned herein are the property of its respective owner. Trademarks may be owned by Drägerwerk AG & Co. KGaA (Dräger) or its affiliates in certain countries and not necessarily in the country in which this material is released. Visit www.draeger.com/trademarks for the current status of Dräger's trademarks.

Corporate Headquarters
Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
■ www.draeger.com

Region Europe
Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
☎ +49 451 882 0
☎ +49 451 882 2080
✉ info@draeger.com

Region Asia Pacific
Dräger Singapore Pte. Ltd.
61 Science Park Road
The Galen #04-01
Singapore 117525
☎ +65 6872 9288
☎ +65 6259 0398

Region Middle East, Africa
Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
☎ +971 4 4294 600
☎ +971 4 4294 699
✉ contactuae@draeger.com

Region Central and South America
Dräger Indústria e Comércio Ltda.
Al. Pucurui - 51 - Tamboré
06460-100 - Barueri - São Paulo
☎ +55 (11) 4689-4900
✉ relacionamento@draeger.com



Locate your Regional Sales
Representative at:
www.draeger.com/contact