

**Ribble Enviro**  
*...everything gas detection*

# Data Sheet

[sales@ribble-enviro.co.uk](mailto:sales@ribble-enviro.co.uk)

+44(0)1200 445 804

[ribble-enviro.co.uk](http://ribble-enviro.co.uk)

Unit 4, Business Park, Gisburn, Clitheroe BB7 4JP

Company No: 06140589 VAT No: GB 906 6241 34



# ALTAIR<sup>®</sup> Single-Gas Detector

Cost-effective, maintenance-free, single-gas detector with a superior lifespan



WE KNOW WHAT'S AT STAKE.

# ALTAIR® Single-Gas Detector

The ALTAIR® Single-Gas Detector is a reliable high-performance single-gas detector with sensor options of H<sub>2</sub>S, CO or O<sub>2</sub>. There is no requirement for maintenance over its lifetime making the ALTAIR an extremely economical instrument.

## Maintenance-Free Service Life

Factory-calibrated detector provides warranted two-years or 1080 alarm minutes (18 hours) of service life with no maintenance. No sensor or battery changes are needed. Built-in gas delivery adapter means no misplaced accessories when conducting gas response tests, avoiding hidden replacement costs.

## Easy To Read Display

The ALTAIR incorporates a simple, easy to read display. The large numeric display allows users to count down instrument life, alarm conditions, set points, peak reading and hours in alarm since activation with accuracy and confidence. The O<sub>2</sub> version can display the current level as well as its highest and lowest readings at a glance.

## Bump Check Indicator

By confirming “Gas Test” with a single button press, the unit allows for a simple bump check, which will be recorded and displayed on the screen as a checkmark for 24 hours. With its built-in gas delivery adapter there are no additional accessories required to carry out a bump check.

## Robust Design

The ALTAIR is IP67 rated and is designed to withstand a 3 m drop test. The extra thick rubberised housing provides protection from accidental drops and helps provide a tight seal, offering simple yet effective resistance to water and dust ingress. Metal screw inserts offer a high level of structural stability over the unit’s lifetime.

## Simple Testing

The detector’s visual, audible and vibrating alarms along with response to a known gas concentration can be checked by ALTAIR QuickCheck. To test the ALTAIR, simply press the button and place it into the test station.

## GALAXY GX2 Automated Test System

The GALAXY GX2 Automated Test System for the ALTAIR single gas detectors is a complete instrument bump test, calibration and record retention system. Options such as industry-standard memory card, wired networking, and receipt printing allow this flexible system to be configured to meet your needs.

More Galaxy GX2 Accessories and Calibration Gas available. Check on [msasafety.com](http://msasafety.com) or reach out to MSA Customer Service.

## Reliable Clip

With the proven suspension clip fitted as standard the ALTAIR can be worn securely anywhere. This rugged clip design keeps the unit attached during even the roughest use.

## Distinctive Alarm System

The superior triple alarm system fitted to the ALTAIR effectively alerts the wearer to any danger. It consists of a distinctive audible alarm of 95 dB at 30 cm, super-bright LEDs visible from a 320° angle and a strong vibration alarm. The numeric display also shows “LO” or “HI” alarm status.

## Event Log

The ALTAIR will record the 25 latest alarm events automatically, offering the ability to assess recent alarm conditions. Connect it to your MSA InfraRed adapter using standard, built-in IR communication. Alarm set points can be adjusted manually prior to the unit’s activation or through IR link after activation.

## Patented Sensors

Patented, MSA Button toxic gas sensors are fitted to both the CO and H<sub>2</sub>S ALTAIR, while the O<sub>2</sub> version accommodates a fast responding 20 series sensor.



## Technical Specifications

<b>Weight</b>	113 g
<b>Dimensions</b>	8.6 cm H x 5.1 cm W x 2.5 cm D
<b>Alarms</b>	As Standard: 95 dB at 30 cm on average, Ultra bright LEDs, Vibrating Alarm
<b>Warranty</b>	2 years after activation, maximum of 18 hours alarm time when activated within 6 months after date of manufacture under normal conditions

<b>Instrument Life</b>	>2 years at an average of 2 minutes of alarm per day
<b>Operating Range</b>	-20°C to +50°C
<b>Humidity</b>	10 – 95% RH non-condensing
<b>Ingress Protection</b>	IP67
<b>Event Logging</b>	25 Latest events
<b>Certifications</b>	ATEX II 2G Ex ia IIC T4 Gb -20°C to +50 °C Europe

## Ordering Information

Detector	1st Alarm	2nd Alarm
<b>Carbon Monoxide [CO] 0–500 ppm</b>		
10092522	25 ppm	100 ppm
10071334	30 ppm	60 ppm
10091171	30 ppm	200 ppm
10071335	35 ppm	100 ppm
10071336	35 ppm	400 ppm
10071337	50 ppm	200 ppm
10071338	100 ppm	300 ppm
<b>Hydrogen Sulphide [H<sub>2</sub>S] 0 –100 ppm</b>		
10092521	10 ppm	15 ppm
10071340	10 ppm	20 ppm
10071361	5 ppm	10 ppm
10071362	8 ppm	12 ppm
10071363	7 ppm	14 ppm
<b>Oxygen [O<sub>2</sub>] 0 –25% Vol</b>		
10071364	18%	19.5%
10092523	19.5%	23.0%
10091172	19.5%	22%
<b>Accessories</b>		
10040002	Clip, Suspender style, black	
10069894	Clip, Suspender Style, Stainless Steel	
10041107	Lanyard kit	
10041105	Cell Phone Belt Clip	
710946	Datadocking FiveStar Link with IR-Jeteye	

<b>Accessories</b>	
467895	Regulator, 0.25 lpm
711175	Regulator, 0.25 lpm, Combination
1003025	Tubing, 40 cm (16")
<b>GALAXY GX2 System Test Stand</b>	
<b>1 VALVE</b> (for use with 1 calibration gas cylinder)	
10128663	UK plus, No-charging
10128653	EU plug, No-charging
<b>4 VALVE</b> (for use with 1-4 calibration gas cylinders)	
10128662	UK plus, No-charging
10128652	EU plug, No-charging
<b>Galaxy GX2 Accessories</b>	
10105756	Electronic cylinder holder
10125135	Non-electronic cylinder holder

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msasafety.com/Trademarks>.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit [MSAsafety.com/offices](https://us.msasafety.com/offices).