

# Dräger Polytron 3000

## Fixed gas detector

The Dräger Polytron 3000 is an intrinsically safe gas detector for the continuous monitoring of more than 60 toxic gases and oxygen in ambient air. It is the part of a new generation of gas detectors developed on a modular platform. Communication to the central control system is done via a 4 to 20 mA signal.



ST-3826-2003

### SIMPLE, QUICK INSTALLATION

The two component concept of a Docking Station and a Dräger Polytron 3000 electronics saves time and money. The Docking Station can be pre-installed – mounting and wiring it into place separately – while protected by a rain and dust cover until commissioning. At commissioning, the Dräger Polytron 3000 electronics is fixed by a quicklock mechanism into the Docking Station, the sensor inserted - and the system is ready for operation.

### EASY TO OPERATE

The Dräger Polytron 3000 is easy to handle with simple maintenance procedures. The DrägerSensors are equipped with a data memory where the calibration information is stored. This allows the Dräger Polytron 3000 to either accept a precalibrated sensor, or the sensor can be calibrated with the transmitter. Digital temperature compensation of the sensor signal is automatically performed.

### WIDE RANGE OF APPLICATION

With unsurpassed RFI resistance and versatile mounting options the Dräger Polytron 3000 is suitable for a wide range of applications.



**Dräger Polytron 3000**  
Intrinsically safe gas detector for toxic gases and oxygen in ambient air.

### Gas

Ammonia	Boron Trichloride	Butadiene
Carbon Monoxide	Chlorine	Diborane
Diethyl Ether	Ethylene Oxide	Germane
Hydrazine	Hydrofluoric Acid	Hydrogen
Hydrogen Chloride	Hydrogen Cyanide	Hydrogen Sulfide
Isopropanol	Nitrogen Dioxide	Nitrogen Monoxide
Oxygen	Ozone	Phosphine
Propylene	Sulfur Dioxide	Tetrahydrofuran

For other gases ask our system centers

**TECHNICAL DATA**

Type	Intrinsically safe transmitter for electrochemical sensors
Gases and Ranges	Toxic gases and oxygen in various ranges
Output	Analog 4 to 20 mA Maintenance signal 3.4 mA constant Fault signal < 3.2 mA
Power Supply	12 to 30 VDC, 2-wire
Ambient Conditions	Transmitter only, for sensors see separate sensor data sheet Temperature - 40 to + 65 °C / - 40 to + 150 °F Pressure 700 to 1300 mbar / 20.7 to 38.4 inch Hg Humidity 0 to 100 %RH, non condensing
Enclosure	IP 66 / 67, NEMA 4, GRP housing, M20 cable gland
Dimensions (approx.)	166 x 135 x 129 mm / 6.54" x 5.32" x 5.08" (H x W x D)
Weight (approx.)	900 g / 2 lbs.
Approvals	ATEX II 1G EEx ia IIC T6/T4: - 40 to + 40 / + 65 °C II 3G EEx nL IIC T6/T4: - 25 to + 40 / + 65 °C II 3D IP6x T65 °C IECEx EEx ia IIC T6/T4: - 40 to + 40 / + 65 °C UL Class I, Div 1, Group A, B, C, D Class II, Div 1, Group E, F, G T6/T4: - 40 to + 40 / + 65 °C CSA Class I, Div 1, Group A, B, C, D Ex ia T6/T4: - 40 to + 40 / + 65 °C CE mark electromagnetic compatibility (directive 89/336/EEC)

**ORDER INFORMATION**

Dräger Polytron 3000 with Display	Various
Dräger Polytron 3000 without Display	Various
Polytron Docking Station, one per transmitter	83 17 990
Duct Mount Kit	83 17 150

**HEADQUARTERS:**

Dräger Safety AG & Co. KGaA  
Revalstrasse 1  
23560 Lübeck, Germany

[www.draeger.com](http://www.draeger.com)

**SYSTEM CENTERS:**

**P. R. CHINA**  
Beijing Fortune Draeger  
Safety Equipment Co., Ltd.  
Yu An Lu A 22, B Area  
Beijing Tianzhu Airport  
Industrial Zone  
Houshayu Shunyi District  
Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80 05

**GERMANY**

Dräger Safety AG & Co. KGaA  
Revalstrasse 1  
23560 Lübeck  
Tel +49 451 882-2794  
Fax +49 451 882-4991

**FRANCE**  
Dräger Safety France SAS  
3c route de la Fédération, BP 80141  
67025 Strasbourg Cedex 1  
Tel +33 3 88 40 59 29  
Fax +33 3 88 40 76 67

**SINGAPORE**

Draeger Safety Asia Pte. Ltd.  
67, Ayer Rajah Crescent # 06 03  
139950 Singapore  
Tel +65 68 72 92 88  
Fax +65 67 73 20 33

**UNITED KINGDOM**  
Draeger Safety UK Ltd.  
Blyth Riverside Business Park  
Blyth, Northumberland NE24 4RG  
Tel +44 1670 352 891  
Fax +44 1670 544 475

**USA**

Draeger Safety, Inc.  
505 Julie Rivers, Suite 150  
Sugar Land, TX 77478  
Tel +1 281 498 10 82  
Fax +1 281 498 51 90