

Dräger CPS 7800 Gas-Tight Suit

The reusable gas-tight Dräger CPS 7800 provides excellent protection against gaseous, liquid, aerosol and solid hazardous substances even in explosive areas. Due to its innovative material and the new suit design it offers increased flexibility and comfort when entering confined spaces and working with cryogenic substances.



Benefits

Gas-tight suit

- SCBA worn over the protective suit
- five suit sizes (S-XXL)
- diagonal zipper for easy donning and doffing without assistance
- suit material D-mex, resusable

Reliable protection

The Dräger CPS 7800 (type 1b) protects against a multitude of possible dangers when dealing with hazardous substances. The antistatic material D-mex[™] offers excellent chemical resistance and protection against mechanical influences. The Dräger CPS 7800 exceeds the requirements of international industry standards for reusable protective suits.

D-mex[™]: 5-fold safety

D-mex[™], the unique suit material, consists of five layers and its reliability has been proven during hazardous substance deployments by the fire service. The middle layer consists of a mechanically extremely strong but flexible textile; on the inside and outside there is a particularly robust elastomer layer, as well as a chemically high-resistant barrier layer. With this design, the suit retains its full protection performance even if the outer material is damaged.

Fitted, flexible and comfortable

The Dräger CPS 7800 increases the wearing comfort even during difficult work in hazardous areas. With its ergonomic cut and five sizes to choose from it offers the highest degree of flexibility for wearers ranging from 1.50 m to 2.05 m in height. In addition, the light and soft suit material adapts ideally for a full range of movement. Offered as an option, individually adjustable braces provide even greater wearing comfort to the user and an improved fit of the suit. A newly designed fit means you don the Dräger CPS 7800 with more ease, can put on and remove the suit by yourself, and shut the zip fasteners without assistance.

Always ready

Time and expense for regular testing could be reduced significantly through innovative materials and new service concepts. The suit can also be cleaned and disinfected automatically without complications. This reduces the effort required to keep the suit ready for use over its lifetime of up to 15 years. An unused suit with face cuff can even be stored for five years without servicing. If repair or maintenance is required, this can be performed by the service technician. Of course, DrägerService is equally happy to perform these tasks.

Ready for the extraordinary

With optional accessories, the Dräger CPS 7800 can be adapted to be even more individual to meet your specific requirements and in turn extend your deployment options further. The suit is available with an

Benefits

integrated Panorama Nova full face mask or face cuff. Stress reduction, especially during prolonged use, can be achieved by equipping the suit with ventilation systems. The Dräger CPS 7800 features an optional ventilation system with the integrated regulating valve PT 120 L that can be connected to different breathing air sources. The suit can also be printed with a customer-specific design, if desired. The Dräger CPS 7800 training suit permits you to perform exercises in realistic scenarios outside contaminated areas with the same equipment characteristics.

System Components



Dräger PSS[®] AirBoss

The Dräger PSS[®] AirBoss offers best in class ergonomics and is one of the lightest weight breathing apparatus for fi refi ghting. Lessons learned from firefighters around the world as well as latest innovations in technology have led us to design an even safer and cleaner SCBA system that enables you to breathe more easily and for longer.



Dräger PAS[®] Filter series

The Dräger PAS[®] filters reliably clean air, e.g. from an existing highpressure network, from liquid and solid particles, including oil vapour and smell.

System Components



Dräger PAS[®] ASV

The Dräger Automatic Switch over Valve (PAS[®] ASV) enables the user to connect compressed air breathing apparatus to an external air supply, such as a factory ring main, and be safe in the knowledge that if the external supply were to fail, there would be a safe and uninterrupted transition to the wearer's back-up air supply.

-1927-2010

Dräger Comfort Vest

Increased performance by up to four hours – without the need for elaborate preparation or logistics: when work gets hot, the Dräger Comfort Vest CVP 5220 is always ready to use as it delivers the cooling action itself. This means: no pre-freezing, no dipping into water, no risk due to dangerous circulating air – and no time loss.



Dräger PAS® AirPack 1

Designed using leading technology and materials, Dräger's range of heavy-duty airline apparatus is ideal for use where an extended duration of breathing air is called for. Chemical tank cleaning, toxic spillages or certain tasks when working on offshore installations are all made easier and more comfortable when using the Dräger PAS[®] AirPack 1.



Dräger HPS® SafeGuard

The Dräger HPS[®] SafeGuard is the extremely lightweight universal helmet for fire and rescue services. Its innovative design combines optimal protection with the highest levels of wearing comfort. Its sporty look, light weight and tailor-made accessories make the helmet a real all-rounder for any challenge.

Accessories

D-4995-2010



Dräger Regulation Valve Dräger PT 120 L (optional)

Cooling effect on the body and additional breathing air from external sources.

Socks with gaiters

Can be worn with the safety boots and, therefore, providing huge flexibility in choosing the right boot.

Laminate + Tricotril combination

Combining mechanical and chemical protection in one – offering high sensitivity, in sizes 10 to 11.



Tricotril[®] over gloves

Cut resistance and chemical protection glove all in one, available in sizes 10 and 11.

Accessories



Rubber ring

For fixing the over glove to the sleeve.

Nitrile-P boots

Firefighter's boots with toecaps, provide excellent protection against penetration, cutting and abrasion. Extra comfortable, in sizes 43 to 50.



Cotton gloves

Optional glove for hygienic wear under chemical protection gloves.



K-MEX[®] Gigant over gloves

Additional cut resistance, available in size 14.

Related Products



Dräger CPS 7900

Tailor-made for use under extreme conditions: The gas-tight Dräger CPS 7900 provides excellent protection against industrial chemicals, biological agents, and other toxic substances. Its innovative material qualifies the CPS 7900 equally well for work in explosive areas and for handling cryogenic substances.

Dräger CPS 5900

The Dräger CPS 5900 is the ideal limited-use, gas-tight chemical protective suit for hazmat incidents. Where complete protection against hazardous gases, liquids and particles is of the utmost priority, this lightweight garment is the suit of choice.



Dräger CPS 5800

The Dräger CPS 5800 is a limited-use chemical protective suit for industrial applications and operations on board that involve a gaseous, liquid or solid hazardous substance.

Technical Data

Suit material		D-mex [™]			
Temperature		During use		-30 °C to +60 °C	
				(temperatures as low	as -80 °C are
				possible for short-terr	m exposure and have
				been tested by Dräge	r for the D-mex™
				material (but not as p	
				approval test))	
		During storage		-30 °C to +60 °C	
Weight		With face cuff and socks		approx. 3.5 kg without ventilation system	
		With face cuff and boots		approx. 5.4 kg without ventilation system	
		With full face mask a	nd socks	approx. 4.3 kg withou	,
		With full face mask a	nd boots	approx. 6.2 kg withou	
APPROVALS					
PPE Regulation (EU) 2016/42	25		Requirements for Pe	ersonal Protective Equip	ment
EN 943-1			EU requirements for gas-tight protective suits for industrial		
			applications		
EN 943-2 (ET)				gas-tight protective suit	s for use by
			firefighters	EU requirements for gas-tight protective suits for use by firefighters	
EN 1073-1				ontamination from radios	active particles
EN ISO 13688			Protection against contamination from radioactive particles Protective Equipment - general requirements		
EN 14126			Protection against contamination from infectious agents		
ISO 16602			International requirements for chemical protective suits		
BS 8467			British requirements for gas-tight NBC protective suits		
SOLAS			Requirements for the use on deep-sea vessels		
			<u> </u>		··•
CHEMICAL TESTS					
Chemical Permea	ation time	Chemical	Permeation time	Chemical	Permeation time
Chemical Permea in min*			in min*		in min*
Chemical Permea in min* Acetone >480		Ethyl acetate	in min* >480	Sarin (GB)**	in min* >1440
Chemical Permea in min*			in min*		in min*
Chemical Permea in min* Acetone >480		Ethyl acetate	in min* >480	Sarin (GB)** Sodium hydroxide	in min* >1440
Chemical Permea in min* Acetone Acetonitrile >480 Acetonitrile >480 Ammonia >480		Ethyl acetate Ethylene oxide	in min* >480 >480	Sarin (GB)** Sodium hydroxide 40 %	in min* >1440 >480
Chemical Permea in min* >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480		Ethyl acetate Ethylene oxide Hydrogen chloride	in min* >480 >480 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)**	in min* >1440 >480 >1440
Chemical Permea in min* >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480		Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)**	in min* >480 >480 >480 >180	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 %	in min* >1440 >480 >1440 >480
Chemical Permea in min* >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480 Chlorine >480		Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol	in min* >480 >480 >480 >180 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene	in min* >1440 >480 >1440 >480 >480
ChemicalPermeain min*AcetoneAcetonitrileAcetonitrileAmmonia1,3-ButadieneCarbon disulphideChlorine>480Dichlormethane>480		Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)**	in min* >480 >480 >480 >180 >480 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran	in min* >1440 >480 >1440 >480 >480 >480 >480
ChemicalPermeain min*AcetoneAcetonitrile>480AcetonitrileAmmonia1,3-Butadiene>480Carbon disulphide>480Chlorine>480Dichlormethane		Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane	in min* >480 >480 >480 >180 >480 >480 >480 >1440 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permea in min* Acetone Acetonitrile Acetonitrile Ammonia 1,3-Butadiene Carbon disulphide Chlorine Dichlormethane >480 Diethylamine Via the constantly updated Drä		Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane	in min* >480 >480 >480 >180 >480 >480 >480 >1440 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permea in min* Acetone Acetonitrile Acetonitrile Ammonia 1,3-Butadiene Carbon disulphide Chlorine Dichlormethane >480 Diethylamine Via the constantly updated Drä	iger VOICE c	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >480 >1440 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permea in min* >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Diethylamine >480 Via the constantly updated Dräwww.draeger.com/voice	iger VOICE c	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >480 >1440 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permea in min* >480 Acetone >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accordation *	iger VOICE c	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >480 >1440 >480	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permeasing in min* >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 I,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Diethylamine >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accordar ** ** Permeation times in accordar ** MECHANICAL TESTS **	iger VOICE c nce with EN 9 ance with FIN	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >1440 >480 >1440 >480 tt about chemical resis	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permeasing in min* >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 I,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accordat ** Permeation times in accordat ** MECHANICAL TESTS Test in accordance with EN 9	iger VOICE c nce with EN 9 ance with FIN	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >480 >480 >480 >480 >480 >480 >1440 >480 It about chemical resis	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permeasing in min* >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 Ammonia >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Diethylamine >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accordar ** ** Permeation times in accordar * MECHANICAL TESTS * Test in accordance with EN 9 Abrasion resistance	iger VOICE c nce with EN 9 ance with FIN	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >480 >480 >480 >1440 >480 about chemical resis Class*** 6	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permeasion in min* Acetone >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accordar ** MECHANICAL TESTS Test in accordance with EN 9 Abrasion resistance Flex-cracking resistance	iger VOICE c nce with EN 9 ance with FIN 243	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >480 >480 >480 >1440 >480 about chemical resis Class*** 6 6	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permeasing in min* Acetone >480 Acetonitrile >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Diethylamine >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accorda * MECHANICAL TESTS * Test in accordance with EN 9 Abrasion resistance Flex-cracking resistance * Flex-cracking resistance at -30 *	iger VOICE c nce with EN 9 ance with FIN 243	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >480 >480 >480 >480 >1440 >480 >1440 >480 about chemical resis Class*** 6 6 6 6	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permeating in min* Acetone Acetonitrile >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Diethylamine >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accordat ** #ECHANICAL TESTS ** Test in accordance with EN 9 Abrasion resistance Flex-cracking resistance * Flex-cracking resistance at -30 * Tear resistance *	iger VOICE c nce with EN 9 ance with FIN 243	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >480 >480 >480 >480 >480 >480 >480 >480 >480 >480 >480 about chemical resist Class*** 6 6 6 3	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440
Chemical Permeasing in min* Acetone >480 Acetonitrile >480 Acetonitrile >480 Acetonitrile >480 Ammonia >480 1,3-Butadiene >480 Carbon disulphide >480 Chlorine >480 Dichlormethane >480 Diethylamine >480 Via the constantly updated Dräwww.draeger.com/voice * * Permeation times in accorda * MECHANICAL TESTS * Test in accordance with EN 9 Abrasion resistance Flex-cracking resistance * Flex-cracking resistance at -30 *	iger VOICE c nce with EN 9 ance with FIN 243	Ethyl acetate Ethylene oxide Hydrogen chloride Lewisite (L)** Methanol Methyl chloride Mustard gas (HD)** n-Heptane latabase you can find ou	in min* >480 >480 >480 >180 >480 >480 >480 >480 >480 >480 >1440 >480 >1440 >480 about chemical resis Class*** 6 6 6 6	Sarin (GB)** Sodium hydroxide 40 % Soman (GD)** Sulphuric acid 96 % Tetrachloroethylene Tetrahydrofuran Toluene VX**	in min* >1440 >480 >480 >480 >480 >480 >480 >1440

**** classes in accordance with EN 943 part 2 - from 1 (lowest) to 6 (highest).

Ordering Information

		Order No.	
Dräger CPS 7800	Blue or orange	R 29 650	
	Olive or beige	R 29 700	
Dräger CPS 7800 Training	Blue (Umex material)	R 29 660	
Sizes	Size S: body heights 1.50 m to 1.65 m	Basic components	
	Size M: body heights 1.60 m to 1.75 m		
	Size L for body heights 1.70 m to 1.85 m		
	Size XL: body heights 1.80 m to 1.95 m		
	Size XXL:body heights 1.90 m to 2.05 m		
Integrated boots or socks	Safety boots: sizes 43 to 50 (German	Basic components	
	sizing system)		
	Gas-tight socks in 3 sizes: 40 to 50		
	(German sizing system)		
Face connection	Face cuff (gas-tight)	Basic components	
	Integrated full face mask		
Gloves	Fluoroelastomer-Butyl (FKM-IIR) gloves:	Basic components	
	sizes 9 to 11		
	Laminate + Triotril glove combination: sizes		
	10 + 11		
	Laminate + Butyl glove combination: sizes		
	10 to 11		
Glove accessories	Cotton gloves	Accessories	
	Gas-tight arm cuff		
	Cut-resistant overgloves Tricotril®		
	K-MEX [®] Gigant		
Ventilation	Regulating valve PT 120 L	Accessories	
Wearing comfort	Braces	Accessories	
Storage and transport	Carry bag	Accessories	
	CPS Storage and transportation bag		
	Storage box		
Customer-specific printing	On thigh, lower arm front or	Accessories	
	Upper arm rear in various colours		
The modular system allows the prote	ective suit to be adapted to the customer's individual re	equirements.	

K-MEX[®] is a registered trademark of KCL GmbH.

Notes

Not all products, features, or services are for sale in all countries. Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA Branch Office P.O. Box 505108 Dubai, United Arab Emirates Tel +971 4 4294 600 Fax +971 4 4294 699 contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd. 61 Science Park Road The Galen #04-01 Singapore 117525 Tel: +65 6872 9288 Fax: +65 6259 0398 asia.pacific@draeger.com

REGION CENTRAL

AND SOUTH AMERICA Dräger Indústria e Comércio Ltda. Al. Pucurui - 51 - Tamboré 06406-100 - Barueri - SP Tel. +55 (11) 4689-4900 relacionamento@draeger.com

