

# The Senko Single Gas Detector SGT-P

Replaceable Sensor & Battery type



**SENKO**



## The most classic detector with a reliable and durable 2 years lifespan and a cost-effective price

The Senko SGT-P Series is a Replaceable single-gas detector that user can replace a sensor or battery after 2-years lifespan. You can turn off the device whenever and battery life signal will let you know when it is time to replace the battery.

High-Sensitivity sensor in SGT-P delivers the real-time reading in ppm (0.1ppm resolution for H2S) and high performing alert provides the ultimate protection from gas poisoning. SGT-P also features a simple menu tree and clear sign of malfunction.

Compatible with IR-Link communication and the Docking Station II, the Senko SGT-P Series is ideal for workers in hazardous areas who need to stay safe with easy way.



## Specification

<b>Model</b>	SGT-P
<b>Sensor Type</b>	Electrochemical
<b>Gas Type</b>	O <sub>2</sub> , H <sub>2</sub> S, CO, NH <sub>3</sub> , H <sub>2</sub> , SO <sub>2</sub> , NO <sub>2</sub>
<b>Measurement</b>	Diffusion type
<b>Display</b>	LCD display
<b>Audible</b>	90dB at 10cm
<b>Warning Lamp</b>	Red Flashing LEDs (Light-Emitting Diode)
<b>Vibration</b>	Vibration Alarm
<b>Battery</b>	Manufacture: Vitzrocell P/N: SB-AA02(P) / System: Lithium Primary Battery Nominal voltage: 3.6V / Nominal capacity: 1.2Ah
<b>Temperature</b>	-40°C ~ +50°C(for Toxic) / -35°C ~ +50°C(for O <sub>2</sub> )
<b>&amp; Humidity</b>	5%~95% RH (Non-condensing)
<b>Case</b>	Rubber Enclosure
<b>Accessories</b>	Calibration Cap, Manual, Calibration and Quality report
<b>Option</b>	External Sampling Pump (SP-Pump101), SENKO-IR Link, Docking Station
<b>Size &amp; Weight</b>	Size: 54(W) × 91(H) × 32(D)mm Weight: 93g(Toxic), 104g(O <sub>2</sub> ) (Battery, clip included)
<b>Operating Life</b>	24 months, based on 2 minutes of alarm per day
<b>Event Log</b>	Recent 30 alarms
<b>Approval</b>	<b>ATEX</b> II 1 G Ex ia IIC T4 Ga <b>IECEX</b> Ex ia IIC T4 Ga <b>INMETRO</b> Ex ia IIC T4 Ga



### Standard Package Contents

- Detector complete with stainless steel alligator clip
- Calibration cap
- User manual
- Calibrate test certification

## Accessories

### SGT-P Docking station

Automatic functional Bump & Calibration test up to 4 units. Save your time and gas usage.



SGT-P Docking station



IR-Link

### IR-Link communication

User can change alarm set points and upload firmware updates and download event logs and perform calibration. For use with SGT series and MGT.

