


TRANSPORTABLE WIRELESS SOLUTIONS.

Have confidence in your local area monitoring

Honeywell BW™ RigRat


Honeywell

HONEYWELL BW™ RIGRAT WIRELESS SYSTEM CONFIGURATIONS




CLOSED-LOOP

- Mesh 868 MHz, 900 MHz or 2.4 GHz system
- Network hops: one alarmed, all alarmed
- Work mode: Router
- One Honeywell BW™ Rigrat can connect up to 8 Honeywell BW™ Rigrats
- Up to 16 units in one system
- Wireless distance on ground level: 984 ft. / 300 m (868-900 MHz) or 492 ft. / 150 m (2.4 GHz)
- Parallel network configuration means no detector is selected as a coordinator and thereby any detector can be taken out of the system without reconfiguration of the wireless network



HONEYWELL BW™ RIGRAT + PORTABLE GAS MONITORS + CONTROLLER

- Mesh 915/868 MHz
- Network hops: 3
- Work mode: RTR (Router)
- Capacity: 64 points (56 STD + 8 RTR)
- Supports RAEPoint
- Supports MultiRAE – MultiRAE lite and MicroRAE
- Connects to Honeywell software
- Ideal for turnaround and rig operations



HONEYWELL BW™ RIGRAT + WI-FI

- Wireless distance on ground level: 164 ft. / 50m LOS
- Location: GPS, 10 m
- Supports n/g Wi-Fi network
- Does not support authentication



HONEYWELL BW™ RIGRAT + BLUETOOTH LOW ENERGY (BLE)

- All Honeywell BW™ Rigrat units are equipped with BLE
- Mobile app simplifies setup and configuration
- Less trained personnel can be dispatched to the unit to update configuration data
- Reduce training times to as low as 20 minutes
- All settings are configured via mobile app
- Email datalog file and calibration certificates via mobile app
- Easy calibration tracking

For More Information

www.honeywellanalytics.com

Brochure_Honeywell BW Rigrat_Wireless-Solutions_DS061119_00_US-EN | 06/19
 Note: Due to ongoing research and product improvement, specifications are subject to change without notice.
 © 2019 Honeywell International Inc.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell